Bull Creek Tech

DisplayPort KVM Cable Kit, 10 ft (3.05 m) / 4K @ 60Hz | 3-in-1 + CAC | NIAP KVM

SKU: KVM10FTV1

UPC 810189122277

- 3-in-1 console cable: DisplayPort + USB-A/B + 3.5 mm audio in one 10-ft lead
- Second 10-ft DisplayPort cable included for dual-monitor workstations
- USB A/B cable feeds the KVM CAC port for smart cards, scanners & fingerprint readers
- UHD 4K x 2K (3840 x 2160) @ 60Hz with true 4:4:4 chroma subsampling
- USB 2.0 (480 Mbps), DisplayPort 1.2, HDCP 2.2 — RoHS compliant

Connect a dual-display workstation to a CAC-enabled NIAP KVM switch with one clean, factory-direct kit. This 10-ft (3.05 m) DisplayPort KVM cable kit bundles three coordinated cables that deliver UHD 4K video, USB peripheral support, and smart-card access in a single, clutter-free installation.

Key Features:

3-in-1 Console Cable: Combines DisplayPort, USB-A/B, and 3.5 mm audio in one 10-ft lead connecting your computer to the KVM.

Dual-Monitor Ready: Includes a second 10-ft DisplayPort cable to drive a second display.

CAC / Smart-Card Support: A dedicated USB A/B cable feeds the KVM CAC port for smart cards, scanners, and biometric/fingerprint readers.

UHD Clarity: Supports 4K x 2K (3840 x 2160) at 60Hz with true 4:4:4 chroma subsampling.

Supported Specs: USB 2.0 up to 480 Mbps, DisplayPort 1.2, and HDCP 2.2.

Technical Specifications

- 3-in-1 DisplayPort + USB-A/B + 3.5 mm Audio KVM cable kit (3 cables)
- Max resolution 3840 x 2160 (4K x 2K) @ 60Hz, 4:4:4 chroma
- DisplayPort 1.2 / HDCP 2.2 / USB 2.0 (up to 480 Mbps)
- 10 ft (3.05 m / 120 in) per cable
- Side A: 3.5mm(M) + DP(M) + USB-A(M); DP(M); USB-A(M)
- Side B: 3.5mm(M) + DP(M) + USB-B(M); DP(M); USB-B(M)
- Operating temp 14° to 122°F (-10° to 50°C); Storage 5° to 140°F (-15° to 60°C)
- 0–90% non-condensing humidity
- Black jacket; RoHS compliant

Warranty

Bull Creek Tech

Limited Warranty