

BCT RUGGED USB Flash Drive / Impact, Heat & Water Resistant | USB 3.1 Gen 1 up to 100MB/s

SKU: RGDUSB



- Extreme durability – pressure/impact resistant up to 250 PSI
- Operates in extreme conditions from 32°F to 225°F
- Water resistant up to 65 ft
- Anti-shock, anti-scratch TPU body
- USB 3.1 Gen 1 high-speed interface, USB 2.0 compatible – up to 10x faster than standard USB 2.0 drives
- Fast transfer speeds up to 100MB/s
- True plug-and-play, hot-swap capable – no software installation
- Backed by a two (2) year warranty

The BCT Rugged USB 3.0 Gen 1 takes external USB flash drives to the next rugged level with extreme performance.

The USB 3.1 Gen 1 high-speed interface is USB 2.0 compatible and can transfer files up to 10 times faster than standard USB 2.0 drives, with speeds up to 100MB/s. Made from a durable anti-shock, anti-scratch TPU compound, this rugged drive is built for endurance.

Technical Specifications

- Capacity:
- Host Interface: USB 3.1 Gen 1 (Compatible with USB 2.0 and USB 3.0) – Universal Serial Bus 3.0/2.0, UHCI
- Transfer Speed: Up to 100MB/s (up to 10x faster than standard USB 2.0 drives)
- Material: Anti-shock and anti-scratch TPU
- Software Installation: None – USB plug-and-play technology
- Uninstall Procedure: None – simply unplug the drive

Capacity	Part Number	UPC	Read Speed	Write Speed
16 GB	RGDUSB-16GB	810189122321	20 MB/s	12 MB/s
32 GB	RGDUSB-32GB	810189122338	30 MB/s	15 MB/s
64 GB	RGDUSB-64GB	810189122345	40 MB/s	20 MB/s
128 GB	RGDUSB-128GB	810189122352	100 MB/s	30 MB/s
256 GB	RGDUSB-256GB	810189122369	100 MB/s	30 MB/s

Bull Creek Tech

512 GB	RGDUSB-512GB	810189122376	100 MB/s	30 MB/s
1 TB	RGDUSB-1TB	810189122383	100 MB/s	30 MB/s

System Requirements

- Compatible: Windows® 10, 8, 7; Mac OS X®
- USB 3.1 port required for USB 3.1 speeds; performance varies by host device

Warranty

Two (2) Year Warranty. Warranty covers the product itself and does not cover data loss or reimbursement for data recovery services. Regular data backups are recommended.

Environmental

- Pressure / Impact Resistant: Up to 250 PSI
- Heat Resistant: Up to 225°F (operating range 32°F to 225°F)
- Water Resistant: Up to 65 feet

Dimensions & Weights

- Dimensions: Coming Soon
- Weight: Coming Soon